

Art. 660V JUNCO Flex® Virgilio



Technical specifications and advantages

- No extension = lower cost
- Only one installation (instead of flex and extension)
- Reduction of the possibility of water loss
- 8-strand stainless steel braid.95% coverage
- Turned female fittings
- Male diam.1/2 very extended and reinforced
- Marked with "CORH" and year of manufacture
- EPDM rubber suitable for the passage of drinking water according to Italian Min. Dec.174:2004
- Pre-assembled gasket on request
- Assembly instructions in the package
- Stainless steel braid diameter 13 mm

Code	Measurement Ø [mm]	Length [cm]
660VMPF120	M.Virg. 1/2-F3/8	20
660VMPF125	M.Virg. 1/2-F3/8	25
660VMPF130	M.Virg. 1/2-F3/8	30
660VMPF135	M.Virg. 1/2-F3/8	35
660VMPF140	M.Virg. 1/2-F3/8	40
660VMPF150	M.Virg. 1/2-F3/8	50
660VMPF160	M.Virg. 1/2-F3/8	60
660VMPF180	M.Virg. 1/2-F3/8	80
660VMPF199	M.Virg. 1/2-F3/8	100
660VMPF220	M.Virg. 1/2-F1/2	20
660VMPF225	M.Virg. 1/2-F1/2	25
660VMPF230	M.Virg. 1/2-F1/2	30
660VMPF235	M.Virg. 1/2-F1/2	35
660VMPF240	M.Virg. 1/2-F1/2	40
660VMPF250	M.Virg. 1/2-F1/2	50
660VMPF260	M.Virg. 1/2-F1/2	60
660VMPF280	M.Virg. 1/2-F1/2	80
660VMPF299	M.Virg. 1/2-F1/2	100
660VMPB20	M.Virg. 1/2-Bicone	20
660VMPB25	M.Virg. 1/2-Bicone	25
660VMPB30	M.Virg. 1/2-Bicone	30
660VMPB35	M.Virg. 1/2-Bicone	35
660VMPB40	M.Virg. 1/2-Bicone	40
660VMPB50	M.Virg. 1/2-Bicone	50
660VMPB60	M.Virg. 1/2-Bicone	60
660VMPB80	M.Virg. 1/2-Bicone	80
660VMPB99	M.Virg. 1/2-Bicone	100