


Punto fisso e componenti Fixed points and components

Art. 997 Rollers for saddle






Technical specifications and advantages

- Cage made of Fe 360
- Roller made of steel
- Aisi 304 stainless steel pin
- Synthesised bronze bushings
- Galvanised white
- To allow the support and longitudinal sliding of insulated and non-insulated pipes
- The support must be installed together with a support saddle

| Code | For pipes of diameter | Payload [N] | A [mm] | B [mm] | C [mm] | E [mm] | F [mm] | H [mm] |
|--------|-----------------------|----------------|-----------|-----------|-----------|-----------|-----------|-----------|
| 997080 | up to 80 mm | 6000 | 89 | 82 | 62 | 40 | 35 | 30 |
| 997180 | 80-180 mm | 10000 | 105 | 95 | 65 | 77 | 50 | 61 |
| 997300 | 180-300 mm | 15000 | 143 | 135 | 99 | 100 | 65 | 76 |

Art. 9975 Saddle for rollers 997





Technical specifications and advantages

- Saddle made of steel
- Galvanised white
- Support element for insulated and non-insulated pipes. Must be combined with a roller support (art. 997)
- Normally it must be welded to the pipeline

| Code | For pipes of diameter | A [mm] | B [mm] | C [mm] | L length [mm] | \$ insulation [mm] | Y [mm] | Payload [N] |
|---------|-----------------------|-----------|-----------|-----------|------------------|--------------------|-----------|----------------|
| 9975080 | up to 80 mm | 60 | 25 | 80 | 200 | 40 | 69 | 6000 |
| 9975180 | 80-180 mm | 60 | 35 | 95 | 300 | 60 | 81 | 10000 |
| 9975300 | 180-300 mm | 92 | 60 | 125 | 300 | 80 | 101 | 15000 |
| | | | | | | | | |

