

Art. 111 StarQuick® Pipe clamp

WATCH THE VIDEO



Technical specifications and advantages

- Patented closure
- Each StarQuick® covers multiple diameters
- Closure without tools, by applying pressure to the pipe
- Ideal for all applications, including corrosive environments or environments subject to atmospheric agents, chemicals, swimming pools, etc.
- High chemical resistance
- Complete tightening around the pipe
- Resistant to UV rays, ageing, oils and petroleum derivatives
- Material: modified polyamide (PA 6), halogen-free
- Suitable from -40° to +90°C
- Complete range from diameter 9.5 to diameter 65.0
- Flammability characteristics according to UL 94-V2
- Grey (RAL 7035) or copper colour. Other colours available upon request
- CE and KIVA certifications (NL)

Code	D [mm]	D (")	D (DN)	Tipo	B [mm]	H [mm]	h [mm]	F _{a,z} [N]	F _{b,z} [N]
Grey colour									
111 0010	10 - 12	1/8	6	SQ-10	29	32	23	170	500
111 0012	11,5 - 15	1/4	8	SQ-12	29	34	23	180	550
111 0015	14 - 16	-	-	SQ-15	29	36	24	200	600
111 0017	16 - 20	3/8	10	SQ-17	29	40	26	230	700
111 0020	20 - 23	1/2	15	SQ-20	29	44	27	270	800
111 0025	24 - 28	3/4	-	SQ-25	40	50	31	280	850
111 0028	27 - 32	-	20	SQ-28	40	53	32	300	900
111 0032	31 - 35	1	-	SQ-32	40	57	34	330	1000
111 0036	35 - 40	-	25	SQ-36	43	66	41	370	1100
111 0040	39 - 44	1 1/4	-	SQ-40	47	70	42	400	1200
111 0047	44 - 50	-	32	SQ-47	52	76	45	430	1300
111 0051	48 - 55	1 1/2	-	SQ-51	57	81	47	470	1400
111 0059	58 - 65	2	40	SQ-59	63	94	55	500	1500

Copper colour									
1160010	10 - 12	1/8	6	SQ-10	29	32	23	170	500
1160012	12 - 15	1/4	8	SQ-12	29	34	23	180	550
1160015	14 - 16	-	-	SQ-15	29	36	24	200	600
1160017	16 - 20	3/8	10	SQ-17	29	40	26	230	700
1160020	20 - 23	1/2	15	SQ-20	29	44	27	270	800
1160025	24 - 28	3/4	20	SQ-25	40	50	31	280	850
1160028	28 - 32	-	-	SQ-28	40	53	32	300	900

