


Attacchi flessibili Flexible hoses

Art. 660 JUNCO Flex® Stainless steel braiding





- 8 wire braid in AISI 304 stainless steel, diameter 13 mm
- Rubber coverage ≥ 95 %
- Brass female fittings
- Bushes in annealed chromed brass or in stainless steel
- Marked with "CORH" and year of manufacture
- Non-toxic EPDM rubber, suitable for the passage of drinking water according to Italian Min. Dec. 174:2004
- Operating temperature from -10 $^{\circ}$ C to +70 $^{\circ}$ C
- Pack of 25 pcs in cardboard box
- Assembly instructions in the package
- Temperature peaks up to 110 °C





Code	Description	L [cm]
660MB115	Male 3/8 x Bicone	15
660MB120	Male 3/8 x Bicone	20
660MB125	Male 3/8 x Bicone	25
660MB130	Male 3/8 x Bicone	30
660MB135	Male 3/8 x Bicone	35
660MB140	Male 3/8 x Bicone	40
660MB150	Male 3/8 x Bicone	50
660MB160	Male 3/8 x Bicone	60
660MB215	Male 1/2 x Bicone	15
660MB220	Male 1/2 x Bicone	20
660MB225	Male 1/2 x Bicone	25
660MB230	Male 1/2 x Bicone	30
660MB235	Male 1/2 x Bicone	35
660MB240	Male 1/2 x Bicone	40
660MB250	Male 1/2 x Bicone	50
660MB260	Male 1/2 x Bicone	60
660MB280	Male 1/2 x Bicone	80
660MB299	Male 1/2 x Bicone	100

Code	Description	L [cm]
660MPB115	Male Extended 3/8 x Bicone	15
660MPB120	Male Extended 3/8 x Bicone	20