


L (mm)	80x80	80x80	80x80	80x80
	1 x F	2 x F	3 x F	Continuo
2,000	6,109	4,587	3,054	12,218
2,250	5,415	4,067	2,707	10,830
2,500	4,858	3,650	2,429	9,716
2,750	4,400	3,099	2,200	8,449
3,000	4,018	2,588	1,856	7,055
3,250	3,693	2,188	1,570	5,966
3,500	3,186	1,870	1,341	5,099
3,750	2,747	1,612	1,156	4,396
4,000	2,386	1,400	1,004	3,818
4,250	2,085	1,223	877	3,336
4,500	1,830	1,074	770	2,929
4,750	1,614	947	679	2,582
5,000	1,427	838	601	2,284
5,250	1,266	743	533	2,025
5,500	1,124	660	473	1,799
5,750	999	586	420	1,599
6,000	888	521	374	1,422


Max carico utile in N, per punto di sospensione (F).

I valori riportati sono validi solo per il profilo.


Il carico utile massimo di tutte le altre parti della costruzione devono essere verificate.




$$A=1/2xL$$



$$A=1/3xL$$



$$A=1/4xL$$




L (mm)	80x80	80x80
	1 x F	Continuo
500	4,877	9,770
550	4,430	8,878
600	4,058	8,135
650	3,742	7,506
700	3,472	6,967
750	3,237	6,499
800	3,032	6,090
850	2,850	5,729
900	2,689	5,407
950	2,544	5,119
1,000	2,414	4,860
1,050	2,286	4,626
1,100	2,079	4,412
1,200	1,740	4,038
1,300	1,476	3,721
1,400	1,266	3,376
1,500	1,096	2,923

Max carico utile in N, per punto di sospensione (F).

I valori riportati sono validi solo per la mensola.

Il carico utile massimo di tutte le altre parti della costruzione devono essere verificate.




L (mm)	100x100	100x100	100x100	100x100
	1 x F	2 x F	3 x F	Continuo
2,000	10,056	7,549	5,028	20,112
2,250	8,919	6,697	4,459	17,838
2,500	8,007	6,014	4,003	16,014
2,750	7,259	5,453	3,629	14,518
3,000	6,633	4,985	3,316	13,267
3,250	6,103	4,552	3,051	12,206
3,500	5,647	3,903	2,800	10,641
3,750	5,250	3,378	2,423	9,210
4,000	4,901	2,947	2,114	8,035
4,250	4,411	2,589	1,857	7,058
4,500	3,897	2,287	1,641	6,236
4,750	3,460	2,031	1,457	5,536
5,000	3,085	1,811	1,299	4,936
5,250	2,761	1,620	1,162	4,417
5,500	2,477	1,454	1,043	3,964
5,750	2,229	1,308	938	3,566
6,000	2,009	1,179	846	3,215
6,500	1,639	962	690	2,622
7,000	1,339	786	564	2,143
7,500	1,093	641	460	1,748
8,000	886	520	373	1,418


Max carico utile in N, per punto di sospensione (F).

I valori riportati sono validi solo per il profilo.


Il carico utile massimo di tutte le altre parti della costruzione devono essere verificate.




$$A=1/2xL$$



$$A=1/3xL$$



$$A=1/4xL$$



L (mm)	100x100	100x100
	1 x F	Continuo
500	6,963	13,947
550	6,325	12,675
600	5,794	11,614
650	5,344	10,717
700	4,959	9,947
750	4,624	9,280
800	4,331	8,696
850	4,072	8,180
900	3,842	7,722
950	3,635	7,311
1,000	3,449	6,941
1,050	3,281	6,607
1,100	3,128	6,302
1,200	2,859	5,769
1,300	2,631	5,317
1,400	2,435	4,929
1,500	2,264	4,592

Max carico utile in N, per punto di sospensione (F).

I valori riportati sono validi solo per la mensola.

Il carico utile massimo di tutte le altre parti della costruzione devono essere verificate.

